

USPS Postage Chart

Effective May 14, 2007

First Class

Up to 1 oz.

Non-Automation	Letters	Flats	Cards
	Basic (Machinable)	.41	.80
3/5 Presort	.373	.699	.241
Automation			
Basic	.36	.686	.22
3-Digit	.334	.484	.204
5-Digit	.312	.383	.191

*Each additional ounce .17

Standard (A)

Reg. (up to 3.3 oz.)

Non-Profit

Non-Profit (up to 3.3 oz.)

Non-Automation	Reg. (up to 3.3 oz.)		Non-Profit (up to 3.3 oz.)	
	Letters	Flats	Letters	Flats
Basic (Machinable)	.255	.699	.164	.389
3/5 Presort	.246	.515	.155	.335

Automation

Basic	.252	.477	.161	.354
3-Digit	.233	.392	.142	-
5-Digit	.218	.335	.127	-

Enhanced Carrier Route

Basic	.226	.249	.157	.180
High Density	.186	.205	.117	.136
Saturation	.177	.187	.108	.118

Additional Destination Discounts

BMC	.033	.033	.033	.033
SCF	.042	.042	.042	.042



HARTY
INTEGRATED SOLUTIONS

Offering you peace of mind in graphic communications from your in-box to your client's mail box.

The Harty Pocket Guide to Automation Compatible Dimensions

First Class Post Cards	Minimum	Maximum
Height	3.5"	4.25"
Length	5"	6"
Thickness	.007"	.016"

Letters (all classes)

Height	3.5"	6.125"
Length	5"	11.5"
Thickness	.009"	.25"

Flats

Height	6"	12"
Length	6"	15"
Thickness	.009"	.75"

- Pieces must be rectangular in shape, with a height-to-length ratio between 1.3 and 2.5.
- Check with your Harty representative or your local USPS Mailpiece Design Analyst for design, folding, and sealing requirements.
- Mailing must be 100% Delivery Point Barcoded.
- Flats can be either Zip + 4 Barcoded or Delivery Point Barcoded.
- Minimum thickness for letters measuring 4.25" x 6" or less is .007".
- Minimum thickness for cards larger than 4.25" x 6" is .009".

This is intended to be used as a guide. Harty takes no responsibility for any errors or deviations in rates. Please check with your Harty representative or your local USPS Mail Acceptance Specialist for more details.



HARTY

INTEGRATED SOLUTIONS

25 James Street • P.O. Box 324 • New Haven, CT 06513
203.562.5112 • 800.654.0562 • Fax 203.782.9168

www.hartynet.com